



ATEX

6'DROP

IEC.



- ATEX & IECEx Zone 2/22 explosive atmosphere certified
- 12th Generation Intel[®] Core[™] i5/i7 Processor
- 10.1" Lumibond display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen with digitizer.
- Enhanced enterprise security with optional Intel vPro[®], Windows Hello face-authentication camera and multifactor authentication options.
- Versatile I/Os connectivity including Thunderbolt[™] 4.
- Support Wi-Fi, 5G, GPS and LTE performance.



SPECIFICATIONS

Operating System Windows 11 Pro

Mobile Computing Platform Intel[®] Core™ i5-1235U Processor Max. 4.4GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

Platform options: Intel[®] Core[™] i5-1245U vPro[®] Processor Max, 4.4GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel[®] Core™ i7-1255U Processor Max. 4.7GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel® Core™ i7-1265U vPro® Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Graphics Intel[®] UHD Graphics

Display

10.1" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200) Protection film 1,000 nits LumiBond display with Getac sunlight readable technology

Storage & Memory

8GB DDR4 Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button 5 tablet programmable buttons Pointing Device

Touchscreen Dual mode touchscreen (multi-touch and digitizer) **Expansion Slot**

Optional (top side): 1D/2D imager barcode reader or HF RFID reader

I/O Interface

I/O Interface SMP webcam x 1ⁱ SMP auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt[™] 4 Type-C x 1 Optional: SIM card slot x 1 (Micro-SIM, 3FF)[×] Optional: Windows Hello face-authentication camera (front-facing) x 1ⁱ

Communication Interface

Dintel® Wi-Fi 6E AX211, 802.11ax Bluetooth (v5.3) " Optional: 4G LTE mobile broadband with integrated GPS ^{III, IV, V} Optional: 5G Sub-6 with integrated GPS ^{III, IV, V} Optional: Dual SIM (Micro-SIM 3FF and e-SIM) ^{III, V} Security Feature

TPM 2.0

IPM 2.0 Kensington lock Optional: Intel[®] vPro[®] Technology Optional: HF RFID reader ⁱⁱⁱ Optional: Windows Hello face-authentication camera (front-facing) ⁱ Optional: Absolute Persistence[®]

Power

AC adapter (65W, 100-240VAC, 50/60 Hz) Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 1 Optional: High capacity Li-ion battery (10.8V, 9240mAh) x 1 Dimension (W x D x H) & Weight

279 x 194.5 x 23.9mm (10.98" x 7.65" x 0.94") ^{vii} 1.38kg (3.04lbs) ^{vii}

Rugged Feature

MIL-STD-810H certified IP66 certified Vibration & 6ft (1.8m) drop resistant viii ATEX & IECEx certified

Environmental Specification

Temperature [™] : - Operating: 0°C to 55°C / 32°F to 131°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Gc Ex II 3D Ex ic op is IIIC T130°C Dc

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version) Optional: Absolute Secure Endpoint Optional: Absolute Secure Access

Optional software

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac Monitoring Getac VGPS Utility *

Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Digitizer pen

Optional: Battery (11.1V, typical 4200mAh; min. 4080mAh) High-capacity Li-ion battery (10.8V, 9240 mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Dual-Bay) AC adapter (65W, 100-240VAC) AC adapter (100W, 100-240VAC) Digitizer pen with tether Anti-static protection film Shoulder strap (2-point) Shoulder strap (2-point) Shoulder hamess (4-point; handsfree) Rotating hand strap with kickstand Rumper-to-Bumper warranty Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment environment, which can cause costiy equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard 3 years Bumper-to-Bumper

UX10-EX FULLY **RUGGED TABLET**

- 5M webcam and optional Windows Hello I. face-authentication camera (front-facing) are mutually exclusive options.
- exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. II.
- III.
- Supports GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in US, UK, EU, AU, and NZ. Units with 4G/5G option come with an embedded SIM IV.
- V. card slot.
- VI. Weight and dimensions vary from configurations and optional accessories
- VII. Drop test results vary from configurations and optional accessories Tested by an independent third-party test lab following MIL-STD-810H. VIII.
- Models require either embedded or standalone GPSmodule. IX.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 115018, Taiwan, R.O.C. Tel : +886 2 2785 7888 globalmarketing@getac.com I www.getac.com

Copyright © 2025 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only,available specification shall be subjected to quotation by request.